



Data extracted from EN 10058

Width b (mm)	Thickness t (mm)								
	5	6	8	10	12	15	20	25	30
	Mass (kg/m)								
10	0.393								
12	0.471	0.565							
15	0.589	0.707	0.942	1.18					
16	0.628	0.754	1.000	1.26					
20	0.785	0.942	1.260	1.57	1.88	2.36			
25	0.981	1.180	1.570	1.96	2.36	2.94			
30	1.180	1.410	1.880	2.36	2.83	3.53	4.71		
35	1.370	1.650	2.200	2.75	3.3	4.12	5.5		
40	1.570	1.880	2.510	3.14	3.77	4.71	6.28	7.85	9.42
45	1.770	2.120	2.830	3.53	4.24	5.3	7.07	8.83	10.6
50	1.960	2.360	3.140	3.93	4.71	5.89	7.85	9.81	11.8
60	2.360	2.830	3.770	4.71	5.65	7.07	9.42	11.8	14.1
70	2.750	3.300	4.400	5.5	6.59	8.24	11	13.7	16.5
80	3.140	3.770	5.020	6.28	7.54	9.42	12.6	15.7	18.8
90	3.530	4.240	5.650	7.07	8.48	10.6	14.1	17.7	21.2
100	3.930	4.710	6.280	7.85	9.42	11.8	15.7	19.6	23.6
120		5.650	7.540	9.42	11.3	14.1	18.8	23.6	28.3
150		7.060	9.420	11.8	14.1	17.7	23.6	29.4	35.3

Figures given here are given for guidance purposes only. While care has been taken to ensure accuracy Duggan Steel (Irl) Ltd. and its related companies do not accept liability for errors / or omissions. Customers should satisfy themselves of the suitability of the products supplied for the use intended.